

JIC 37° Flare (SAE J514)

Female | Swivel Continued


Descriptive #	Product #	SAP #	Hose Size ID		Thread Size (A)	Hex-1 Wrench Size	Hex-2 Wrench Size	Cut-Off (C)		Length (L)		Skive Type	SR15N, DR15N, SFS	SR25N, DR25N, LR25N	SR16SC, XR16SC, ARC16SC, DR16SC	SCP3, XCP3, ACP3	XCP4		
			in.	mm	in.	mm	in.	mm	in.	mm	in.		mm						
B2-JCFX-1612	14400-1612	20241921	1	25.4	1½-12	1¼	32	1¼	32	1.88	47.7	3.65	92.8	NS	Y	Y	Y	Y	
B2-JCFX-1616	14400-1616	20241916	1	25.4	1½-12	1½	38	1¼	32	1.96	49.8	3.74	94.9	NS	Y	Y	Y	Y	
B2-JCFX-1616S	14400-1616S	20286843	1	25.4	1½-12	1½	38	1¼	32	1.96	49.8	3.74	94.9	NS	Y	Y	Y	Y	
B2-JCFX-1620T	14400-1620	20241919	1	25.4	1½-12	2	50	1½	41	2.07	52.5	3.84	97.6	NS	Y	Y	Y	Y	
S4-JCFX-2020T	28400-2020	20241915	1¼	31.8	1½-12	2	50	1½	41	2.15	54.6	4.20	106.6	NS	Y	Y	Y		
S4-JCFX-2020S	28400-2020S	20289599	1¼	31.8	1½-12	2	50	1½	41	2.15	54.6	4.20	106.6	NS	Y	Y	Y		
S4-JCFX-2024T	28400-2024	20293262	1¼	31.8	1½-12	2¾	55	2	50	2.45	62.1	4.49	114.1	NS	Y	Y	Y		
S4-JCFX-2424T	28400-2424	20241928	1½	38.1	1½-12	2¾	55	2	50	2.42	61.4	4.75	120.6	NS	Y	Y			
S4-JCFX-2424S	28400-2424S	20289598	1½	38.1	1½-12	2¾	55	2	50	2.42	61.4	4.75	120.6	NS	Y	Y			
S4-JCFX-3232T	28400-3232	20242028	2	50.8	2½-12	2¾	70	2¾	65	2.88	73.1	5.71	145.1	NS	Y	Y			
S4-JCFX-3232S	28400-3232S	20739385	2	50.8	2½-12	2¾	70	2¾	65	2.88	73.1	5.71	145.1	NS	Y	Y			

T: Thrust-Wire Nut (see "Fitting Identification" in Appendix for details)

S: Stainless Steel

JIC 37° Flare (SAE J514)

Female | 45° Elbow | Swivel



S=Skive

NS=Non-Skive

DG=Dual-Grip™

Descriptive #	Product #	SAP #	Hose Size ID		Thread Size (A)	Hex-1 Wrench Size	Drop (D)	Cut-Off (C)		Length (L)		Skive Type	SR15N, DR15N, SFS	SR25N, DR25N, LR25N	SR16SC, XR16SC, ARC16SC, DR16SC	SCP3, XCP3, ACP3	XCP4		
			in.	mm	in.	mm	in.	mm	in.	mm	in.		mm						
B2-JCFX45-0404	14420-0404	20241948	1/4	6.4	7/16-20	5/8	16	0.39	10	1.46	37.0	2.44	61.9	NS	Y	Y	Y	Y	Y
B2-JCFX45-0405	14420-0405	20241962	1/4	6.4	1/2-20	11/16	17	0.47	12	1.46	37.0	2.44	61.9	NS	Y	Y	Y	Y	Y
B2-JCFX45-0406	14420-0406	20241949	1/4	6.4	9/16-18	3/4	19	0.43	11	1.54	39.0	2.52	63.9	NS	Y	Y	Y	Y	Y
B2-JCFX45-0606	14420-0606	20241950	3/8	9.5	9/16-18	3/4	19	0.43	11	1.81	46.0	2.86	72.6	NS	Y	Y	Y	Y	Y
B2-JCFX45-0608	14420-0608	20241954	3/8	9.5	3/4-16	1	25	0.59	15	1.85	47.0	2.90	73.6	NS	Y	Y	Y	Y	Y
B2-JCFX45-0808	14420-0808	20241963	1/2	12.7	3/4-16	1	25	0.59	15	2.05	52.0	3.29	83.7	NS	Y	Y	Y	Y	Y
B2-JCFX45-0810	14420-0810	20241965	1/2	12.7	7/8-14	1½	27	0.63	16	2.01	51.0	3.26	82.7	NS	Y	Y	Y	Y	Y
B2-JCFX45-1010	14420-1010	20241980	5/8	15.9	7/8-14	1½	27	0.75	19	2.44	62.0	3.92	99.5	NS	Y	Y	Y	Y	Y
B2-JCFX45-1012	14420-1012	20241967	5/8	15.9	1½-12	1¼	32	0.83	21	2.72	69.0	4.07	103.5	NS	Y	Y	Y	Y	Y
B2-JCFX45-1212	14420-1212	20241951	3/4	19.0	1½-12	1¼	32	0.83	21	2.64	67.0	4.19	106.5	NS	Y	Y	Y	Y	Y
B2-JCFX45-1216	14420-1216	20241953	3/4	19.0	1½-12	1½	38	1.02	26	2.80	71.0	4.35	110.4	NS	Y	Y	Y	Y	Y
B2-JCFX45-1612	14420-1612	20293221	1	25.4	1½-12	1¼	32	1.18	30	2.76	70.0	4.53	115.1	NS	Y	Y	Y	Y	
B2-JCFX45-1616	14420-1616	20241957	1	25.4	1½-12	1½	38	0.94	24	3.11	79.0	4.89	124.1	NS	Y	Y	Y	Y	
S4-JCFX45-2020T	28420-2020	20241961	1¼	31.8	1½-12	2	50	1.46	37	3.82	97.0	5.87	149.0	NS	Y	Y	Y		
S4-JCFX45-2424T	28420-2424	20241960	1½	38.1	1½-12	2¾	55	1.69	43	4.45	113.0	6.78	172.2	NS	Y	Y			