



PURE GUM RUBBER 40 DUROMETER



Colour

Tan

Finish

Smooth

Physical Characteristics

Tensile: 2300 PSI

Elongation: 600%

Hardness: 40 SHORE "A" +/- 5

Temperature Range: -40°C to 70°C (-40°F to 158°F)

Notes

A soft, long wearing non-marking natural rubber. Pure gums have excellent abrasion and tear resistance. It also has superior resilience, tensile and elongation characteristics. Gum rubber is also excellent on all steel surfaces against abrasion. Pure gum is not suitable for outdoor or oil resistant applications. it is also used for gasket and sand/shot blast curtain manufacturing. Pure Gum Rubber has excellent adhesion to fabric and metal. it is widely used to manufacture sleeves for chutes on current mixers.

ISO/ASTM DESIGNATION = NR

Parts No.	Gauge x Width	Length	Wt. Per SF lbs.
PGI-063-48	1/16" X 48"	100FT	0.34
PGI-125-48	1/8" X 48"	66FT	0.68
PGI-188-48	3/16" X 48"	66FT	1.02
PGI-25-36	1/4" X 36"	66FT	1.36
PGI-25-48	1/4" X 48"	66FT	1.36
PGI-375-48	3/8" X 48"	50FT	2.02
PGI-5-48	1/2" X 48"	50FT	2.71
PGI-75-48	3/4" X 48"	50FT	4.07
PGI-1-48	1" X 48"	50FT	5.41