

LINCOLN PNEUMATIC COUPLING

Features

- Lincoln Long-Nose Automotive Interchange 2SHDS3 4SHDS3 4SHDS4
- Interchanges with Parker 70-Series, Tomco Series-1110, Coilhose Type-17

Specifications

- Pressure rating: 300 PSI
- Temperature range: -40°F to 250°F (-40°C to 121°C)

It is important to be safe when installing quick disconnect couplings into a pneumatic. circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure

		Female Threaded Plug	
	Body Size	Threads	Steel Part #
—	1/4	1/4" - 18 NPT	L2F2
		Male Threaded Plug	
	Body Size	Threads	Steel Part #
autu.	1/4"	1/4"- 18 NPT	L2M2
	Fe	emale Threaded Coupler	W()(I)
	Body Size	Threads	Brass Part #
	1/4"	1/4" - 18 NPT	2LF2-B
	N	Male Threaded Coupler	
	Body Size	Threads	Brass Part #
	1/4"	1/4" - 18 NPT	2LM2-B



Address: 2502 Elm Street | Sudbury, ON | P3E 4R6

Phone: 705-682-3389 | Email: info.mcc@mansourgroup.inc

www.mansourgroup.inc