



Piranha Hose 2500 PSI

Piranha® hose is constructed from materials selected to provide rugged and reliable service under even the most severe and demanding conditions found in high pressure sewer cleaning. A polyether-urethane cover provides exceptional cut, abrasion and fungus resistance. Tube, reinforcement, and cover layers are bonded together to maximize fitting retention and extend operation life. Piranha® hose cover colors conform to industry standards for maximum operating pressure ratings. Standard hose lengths come on reels with male NPT fittings installed.



1

<u>Part Number</u>	<u>Size Code</u>	<u>Hose ID</u>	<u>Male NPTF Nom. Thread Size</u>	<u>Working Press. (Max.)</u>	<u>Assembled Length</u>	<u>Wt. Per Pkg.</u>
<u>SPOR-MM12X400</u>	12	3/4 in	3/4-14	2500 psi	400 ft	112 lbs
<u>SPOR-MM12X500</u>	12	3/4 in	3/4-14	2500 psi	500 ft	140 lbs
<u>SPOR-MM12X600</u>	12	3/4 in	3/4-14	2500 psi	600 ft	168 lbs
<u>SPOR-MM12X800</u>	12	3/4 in	3/4-14	2500 psi	800 ft	224 lbs
<u>SPOR-MM16X200</u>	16	1 in	1-11 1/2	2500 psi	200 ft	80 lbs
<u>SPOR-MM16X300</u>	16	1 in	1-11 1/2	2500 psi	300 ft	120 lbs

<u>Part Number</u>	<u>Size Code</u>	<u>Hose ID</u>	<u>Male NPTF Nom. Thread Size</u>	<u>Working Press. (Max.)</u>	<u>Assembled Length</u>	<u>Wt. Per Pkg.</u>
<u>SPOR-MM16X400PR</u>	16	1 in	1-11 1/2	2500 psi	400 ft	160 lbs
<u>SPOR-MM16X500PR</u>	16	1 in	1-11 1/2	2500 psi	500 ft	200 lbs
<u>SPOR-MM16X600</u>	16	1 in	1-11 1/2	2500 psi	600 ft	240 lbs
<u>SPOR-MM16X600PR</u>	16	1 in	1-11 1/2	2500 psi	600 ft	240 lbs
<u>SPOR-MM16X700</u>	16	1 in	1-11 1/2	2500 psi	700 ft	280 lbs
<u>SPOR-MM16X800PR</u>	16	1 in	1-11 1/2	2500 psi	800 ft	320 lbs
<u>SPOR-MM16X900</u>	16	1 in	1-11 1/2	2500 psi	900 ft	370 lbs
<u>SPOR-MM16x1000</u>	16	1 in	1-11 1/2	2500 psi	1000 ft	400 lbs
<u>SPOR-MM20X400</u>	20	1 1/4 in	1 1/4-11 1/2	2500 psi	400 ft	241 lbs
<u>SPOR-MM20X500</u>	20	1 1/4 in	1 1/4-11 1/2	2500 psi	500 ft	295 lbs
<u>SPOR-MM20X600</u>	20	1 1/4 in	1 1/4-11 1/2	2500 psi	600 ft	354 lbs
<u>SPOR-MM20X800WR</u>	20	1 1/4 in	1 1/4-11 1/2	2500 psi	800 ft	580 lbs

Construction: Tube: Smooth, thermoplastic elastomer blend.

Cover: Orange, smooth, abrasion resistant 0.05" thick urethane. Reinforcement: One or two braids of high strength synthetic fiber.

Temperature Range: -40°C (-40°F) to +66°C (151°F)

Cut Method: Ratchet Cutter (<2"ID) Safety Scissors - Wear Safety Gloves