



SHJ Jack Hose

SHJ is designed for extreme high-pressure hydraulic lines for jacking systems.

Performance + Specs

- Meets flame resistance
 - USMSHA Designation
 - 2:1 Safety Factor
- Inner Tube
 - Nitrile (NBR) Black
- Reinforcement
 - Two braids of high-tensile steel wire
- Cover
 - CR (Polychloroprene) Black
- Temperature Range
 - 40F to 212F

Key Features

Flame Resistance

Branding

Continental SHJ-04 Jack Hose 1/4" (6.4 MM) 10000 PSI (68.9 MPa) MSHA 2G-14C/12 MADE IN USA

SHJ Jack Hose

Product Numbers															
SAP	Product #	ID	ID		OD		Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)	
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa			
20319601	SHJ-04	1/4	0.25	6.40	0.58	14.70	10000	68.9	4.00	102.00	20000	137.90	B2	0.24	
20319602	SHJ-06	3/8	0.38	9.50	0.74	18.70	10000	68.9	5.00	127.00	20000	137.90	B2	0.3	

SAP Number		Fitting Description
20242067		B2-NPM-0604
20242109		B2-NPM-0406
20242115		B2-NPM-0408
SAP Number		Fitting Description
20242069		B2-NPM-0606
20242110		B2-NPM-0402
20286649		B2-NPM-0404S
SAP Number		Fitting Description
20242079		B2-NPM-0608
20242111		B2-NPM-0404
20286830		B2-NPM-0606S