



VELOCITY WATER TRANSFER

Velocity™ Water Transfer Hose gets water where you need it, efficiently and fast. This tough clear PVC hose lets you see water in motion, even in the most demanding applications. The premium heavy-duty construction provides great durability. Whether you need full-suction or transfer, the Velocity™ WT is the hose for your job-site.

Performance + Specs

Construction Tube Flexible Smooth PVC	Cover Corrugated PVC, Also available with a Static Wire
Reinforcement Rigid PVC Helix; Synthetic Braiding	Temperature Range -13°F / -25°C ~ 158°F / 70°C
Design Factor 3:1	Coupling Refer to the Continental ContiTech Industrial Hose Assembly Manual for crimp specifications.

Branding

VELOCITY WATER TRANSFER

Order Codes: 591-101

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Bend Radius (in.)	Bend Radius (mm)	Vacuum HG (in.)	Vacuum HG (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	2.05	52.10	100	2.5	63.50	29	737	110	0.76	0.66	0.98	20762594
2	50.80	2.52	64.20	100	4	101.60	29	737	100	0.69	0.72	1.07	20762595
3	76.20	3.72	94.70	100	6	152.40	29	737	100	0.69	1.42	2.12	20635650
4	101.60	4.71	119.70	60	7	177.80	29	737	75	0.52	1.56	2.32	20761726
				100	7	177.80	29	737	75	0.52	1.56	2.32	20635651
6	152.40	7.19	182.70	20	10	254.00	29	737	70	0.48	4.29	6.38	20761729
				60	10	254.00	29	737	70	0.48	4.29	6.38	20762596
				100	10	254.00	29	737	70	0.48	4.29	6.38	20630166
8	203.20	9.29	236.00	20	15	381.00	29	737	60	0.41	6.01	8.94	20761732
				40	15	381.00	29	737	60	0.41	6.01	8.94	20780736