



BLUE FLEXWING®

Continental Blue Flexwing® handles the majority of today's industrial chemicals in pressure, gravity flow or suction service.

Performance + Specs

Construction Tube

- Spectar® (XLPE) Cross-Linked Polyethylene

Cover

- EPDM Rubber (Wrapped Finish)

Reinforcement

- Spiral-Plied Synthetic Fabric
- Double Wire Helix

Temperature Range

- -25°F / -32°C ~ 150°F / 66°C

Design Factor

- 4:1

Packaging

- Coiled & Poly-Wrapped

Coupling

- Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service

Branding

Blue Flexwing®

Order Codes: 546-066 (1/2" - 4")

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum HG (in.)	Vacuum HG (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.10	1.22	31.00	100	Blue	7.00	178.00	29	737	200	1.38	0.45	0.67	20018504
1	25.40	1.47	37.30	100	Blue	8.00	203.00	29	737	200	1.38	0.55	0.82	20018506
1-1/4	31.80	1.75	44.50	100	Blue	9.00	229.00	29	737	200	1.38	0.70	1.04	20018512
1-1/2	38.10	2.04	51.80	100	Blue	10.00	254.00	29	737	200	1.38	0.95	1.41	20018517
2	50.80	2.58	65.50	100	Blue	12.00	305.00	29	737	200	1.38	1.22	1.82	20018524
2-1/2	63.50	3.13	79.50	100	Blue	15.00	381.00	29	737	200	1.38	1.65	2.46	20018530
3	76.20	3.70	94.00	100	Blue	18.00	457.00	29	737	200	1.38	2.24	3.33	20018535