



PYROFLEX II HOT AIR

For conveying hot air from compressors to tanks on bulk dry material carriers.

Performance + Specs

Construction Tube Black Heat-Resistant EPDM Synthetic Rubber	Cover Heat-Resistant Black EPDM Synthetic Rubber with Orange Spiral Stripe (Wrapped Impression)
Reinforcement Spiral-plied Synthetic Fabric with Wire Helix	Temperature Range -20°F / -29°C ~ 325°F / 163°C
Design Factor 4:1	Packaging 100' lengths, coiled and polywrapped
Coupling Refer to the Continental ContiTech Industrial Hose Assembly Manual for crimp specifications	Non Stock / Sizes For special production run minimum requirements, see Appendix D.

Branding

PYROFLEX II HOT AIR

Order Codes: 549-394, 541-394, 541-394, 541-394

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum HG (in.)	Vacuum HG (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.55	64.80	100	Black	5	127	29	737	100	0.69	1.22	1.820	20019669
3	76.20	3.55	90.20	100	Black	7	178	29	737	100	0.69	1.93	2.870	20019671
4	101.60	4.61	117.10	100	Black	10	254	29	737	100	0.69	2.65	3.940	20019674
6	152.40	6.74	171.10	100	Black	30	750	29	737	100	0.69	4.80	7.150	20019675
8	203.00	9.02	229.00	20	Black	48	1220	29	737	100	0.69	9.2	10.68	
12	305.00	13.23	336.00	20	Black	72	1830	29	737	100	0.69	18.4	27.23	