

Betts Wet-R-Dri™ Butterfly Valves

Application

• Designed for handling liquid, gaseous, or dry products

Features

- Has a positive stop in the open and closed position
- Detent spring and ball assist in holding the disc in the open and closed position
- Drilling fits TTMA recommended standards
- Opens by turning hand 1/4 turn counter clockwise

Specification

• Temperature range: 0°F to 400°F (-18°C to 204°C)

Manual



Size	Maximum Working Pressure PSI	Extruded aluminum body with FKM-B disc Part #
2"		WD201ALVB
3"		WD301ALVB
4"	75	WD401ALVB
5"	75	WD501ALV
6"		WD601ALV
8"		WD801ALV

Metering



Size	Maximum Working Pressure PSI	Extruded aluminum body with FKM-B disc Part #
2"		WD206ALVB
3"		WD306ALVB
4"	75	WD406ALVB
5"	75	WD506ALV
6"		WD606ALV
8"		WD806ALV

Replacement Handles

Part #	Description	
28967ALEY	replacement handle for 2", 3", 4", and 5" manual handle valves	
25933AL	replacement handle for 6" and 8" manual handle valves	
28981ALEY	replacement handle for 2", 3", 4", and 5" metering handle valves	
26287AL	replacement handle for 6" and 8" metering handle valves	

NOTE: For flange dimensions, diagrams and additional information please reference dixonvalve.com.



Address: 2502 Elm Street | Sudbury, ON | P3E 4R6 Phone: 705-682-9900 | Email: info.mcc@mansourgroup.inc www.mansourgroup.inc