

Series N600 | Dual Hose

• Hydraulics • Spray Painting • Air/Water



To handle dual 1/4" through 1/2" I.D. hose.

- Narrow frame and compact mounting base.
- Non-sparking ratchet assembly.
- Declutching arbor to prevent damage from reverse winding.
- Standard inlets: 90° full-flow swivel joints with Viton® seals, 1/2" female NPT threads.
- Optional balanced pressure (BP) swivel joints are available upon request. Subtract 1-3/4" from "F" dimension.
- Standard outlets: 1/2" female NPT threads.
- Standard pressures to 3000 psi (207 bar), available up to 10,000 psi (690 bar) – must specify.
- Standard fluid temperatures from -40° F to +250 °F (-40° C to +121° C). Optional temperature ratings available - consult factory.
- 4-way roller assembly. SR position is standard, other configurations available, must specify.
- Constant tension is available – consult factory.
- Reels for use with oxygen/acetylene. See Series N400 on page 8.



Standard SR configuration shown

PARTS DRAWING – ISO 80

Model Number	Hose Capacity of Reel shown in feet /meter				Approx. Weight shown in lb/kg			Standard Roller Assy.	Reel Dimensions*** shown in inches/millimeter								
	I.D. in. mm	1/4 6	3/8 10	1/2 13	NET	UPS/ FedEx SHIP Wt.	Freight SHIP Wt.		A	B	C	E	F Full-Flow	F BP	G	H	X
	O.D. in. mm	5/8 16	3/4 19	7/8 22													
N615-19-20-10.5C		2/35	2/35	2/20	63	74*	98	N203	9	3	10.5	20.75	14	12.25	20	10.62	7
		2/11	2/11	2/6	29	34	44		229	76	267	527	356	311	508	270	178
N617-19-20-10.5J		2/50	2/50	2/25	66	84*	101	N205	11	5	10.5	20.75	16	14.25	20	10.62	9
		2/15	2/15	2/8	30	38	46		279	127	267	527	406	362	508	270	229
N615-23-24-10.5B		2/65	2/60	2/30	87	—	122	N203	9	3	10.5	24	14	12.25	24	12.62	7
		2/20	2/18	2/9	40	—	55		229	76	267	610	356	311	610	321	178
N617-25-26-15.5B		2/75	2/75	2/50	93	—	128	N205	11	5	15.5	25.5	16	14.25	26	13.62	9
		2/23	2/23	2/15	42	—	58		279	127	394	648	406	362	660	346	229
N617-25-26-15.5A		2/100	2/85	—	120	—	155	N205	11	5	15.5	25.5	16.75	15	26	13.62	9
		2/31	2/26	—	54	—	70		279	127	394	648	425	381	660	346	229

Notes:

A hose stop is necessary to keep spring from unwinding.

1. Specifications subject to change.
2. Reel models and capacities shown are for standard drag applications; for vertical lift applications, consult factory.
3. Other sizes, from standard components, available on request.
4. Finish: Refer to page 3.

5. Be sure to check dimensions and weights prior to ordering.

NOTICE: A flexible connector must be used between the inlet pipe and the inlet swivel joint.
*Dimensional weight may apply when shipped as a parcel package (via FedEx or UPS Ground).

*** X, Y indicate mounting holes. See page 5.

For hydraulic tool circuit applications, full flow swivels with Viton® seals are recommended.

Available Roller Positions



SR (STD)



VR (OPT)



TR (OPT)



TR (Wallmount)

