

Series 800

- Fuel Dispensing (Consult Factory)
- Waste Oil Evacuation • Air/Water

To handle 3/4" or 1" I.D. hose.

- Rollformed channel frame for heavy-duty applications.
- Non-sparking ratchet assembly.
- Declutching arbor to prevent damage from reverse winding.
- Standard inlet: 90° balanced pressure swivel joint, 1" female NPT threads.
- Standard outlet: 1" female NPT threads.
- Standard pressures to 2000 psi (138 bar), available up to 6000 psi (414 bar) – must specify.
- Standard fluid temperatures from -40° F to +250 °F (-40° C to +121° C). Optional temperature ratings available - consult factory.
- 4-way roller assembly. SR and VR roller positions: swivel joint is standard on the right. TR roller positions: swivel joint is standard on the left. Other configurations available, must specify.
- Constant tension is available – consult factory.



Standard SR configuration shown

PARTS DRAWING – ISO 42

Model Number	Hose Capacity of Reel shown in feet /meter			Approx. Weight shown in lb/kg		Standard Roller Assy.	Reel Dimensions*** shown in inches/millimeter									
	I.D. in. mm	3/4 19	1 25	NET	SHIP		A	B	C	D	E	F	G	H	X	Y
	O.D. in. mm	1-9/32 33	1-1/2 38													
†818-23-24-10.5J		50† 15†	25† 8†	87 39	122 55	R206	11.25 286	6 152	10.5 267	24.5 622	22.75 578	15.62 397	23.88 607	12.5 318	6.5 165	20 508
816-25-26-10.5B		50 15	35 11	96 44	131 59	R204	9.25 235	4 102	10.5 267	26.25 667	24.75 629	13.62 346	25.88 657	13.5 343	4.5 114	21.75 552
818-25-26-10.5B		– –	50 15	102 46	137 62	R206	11.25 286	6 152	10.5 267	26.25 667	24.75 629	15.62 397	25.88 657	13.5 343	6.5 165	21.75 552
818-25-26-10.5 SD		75 23	– –	110 46	145 66	R206	11.25 286	6 152	10.5 267	26.25 667	24.75 629	16.38 416	25.88 657	13.5 343	6.5 165	21.75 552
820-25-26-10.5A		– –	75 23	131 59	166 75	R308	13.25 337	8 203	10.5 267	27 686	24.75 629	18.38 467	25.88 657	13.5 343	8.5 216	21.75 552
820-30-31-10.5A		– –	100 30	137 62	172 78	R308	13.25 337	8 203	10.5 267	30.5 775	28.75 730	18.38 467	31.38 797	17 432	8.5 216	25.25 641
820-30-31-15.5A		100 30	– –	145 66	180 82	R308	13.25 337	8 203	15.5 394	30.5 775	28.75 730	18.38 467	31.38 797	17 432	8.5 216	25.25 641

Notes:

A hose stop is necessary to keep spring from unwinding.

- Specifications subject to change.
- Reel models and capacities shown are for standard drag applications; for vertical lift applications, consult factory.
- Other sizes, from standard components, available on request.
- Finish:** Refer to page 3.

5. Be sure to check dimensions and weights prior to ordering.

NOTICE: A flexible connector must be used between the inlet pipe and the inlet swivel joint.

*** X, Y indicate mounting holes. See page 5.

†Capacity based on low pressure air hose only.

Available Roller Positions



SR (STD)



VR (OPT)



TR (OPT)



TR (Wallmount)

