


SBR RUBBER 60 DUROMETER

Colour

Black

Finish

Smooth

Physical Characteristics

Tensile: 500 PSI

Elongation: 300%

Hardness: 60 SHORE "A" +/- 5

Temperature Range: -30°C to 77°C (-22°F to 170°F)

Notes

An economical. General-purpose 60 Durometer rubber sheet, this rubber offers solid resistance to abrasion and impact. It is not recommended for applications where oil or gasoline is present. SBR rubber sheet has good vibration and sound insulating properties.

COMMERCIAL RECYCLED RUBBER ISO/ASTM DESIGNATION= SBR

Parts No.	Gauge x Width	Length	Wt. Per SF lbs.
SBR160-.063-36	1/16" X 36"	100FT	0.47
SBR160-.063-48	1/16" X 48"	100FT	0.47
SBR160-.094-48	3/32" X 48"	66FT	0.71
SBR160-.125-36	1/8" X 36"	66FT	0.94
SBR160-.125-48	1/8" X 48"	66FT	0.94
SBR160-.188-36	3/16" X 36"	66FT	1.41
SBR160-.188-48	3/16" X 48"	66FT	1.41
SBR160-.25-36	1/4" X 36"	50FT	1.89
SBR160-.25-48	1/4" X 48"	50FT	1.89
SBR160-.375-36	3/8" X 36"	50FT	2.83
SBR160-.375-48	3/8" X 48"	50FT	2.83
SBR160-.5-36	1/2" X 36"	50FT	3.77
SBR160-.5-48	1/2" X 48"	50FT	3.77
SBR160-.5-60	1/2" X 60"	50FT	3.77
SBR160-.625-48	5/8" X 48"	50FT	4.71
SBR160-.75-48	3/4" X 48"	50FT	5.66
SBR160-1-48	1	50FT	7.54
SBR160-1.25-48	1-1/4" X 48"	9FT	9.43
SBR160-1.5-48	1-1/2" X 48"	9FT	11.32
SBR160-2-48	2" X 48"	9FT	15.09